

VEER HYBRID

TECHNICAL SPECIFICATIONS

Dimensions

- 4940 mm Length
- 1650 mm Height
- 1950 mm Width
- 3030 mm Wheelbase

Battery

- 90 kWh

Acceleration

- 4.9 seconds 0-100 km/h

Top speed

- 160 km/h (Limited)

Range

- 500+ km

Fast charging

- 80% in 30 minutes

Drive

- All wheel drive, Dual Motor
- 620 Nm Torque

Ground clearance

- 265 mm

Seating

- 4 or 8 depending on configuration

Maximum gradient

- 40°

Accessories

- Highlift Jack
- Sand ladder
- Thermal imaging
- Weapon mount
- IP 65 storage for equipment & gear

Kerb weight

- 1870 kg

Payload

- 690 kg

Weight distribution

- 50.5 : 49.5 (Fr : Rr)
- 45 : 55 (Fr : Rr) @ gross weight

Angle of approach

- 34°

Ramp breakover

- 19°

Angle of departure

- 30°

Transverse angle

- 55°

Turning radius

- 6 m

Exteriors

- Blackout package
- Composite shield doors with armour package
- Winch
- Heavy duty tow hooks

Exteriors (no door)

- Safety nets for doors
- Raw shell with no window
- Camo capability

Wheels

- 255/65 R18
- Run-flat tyres

Water wading capability

- 900 mm

Operating temperature range

- -20° to +60° C

Towing

- 2500 kg (Trailer nose weight 160kg)

Suspension

- Independent double wishbone (Front & Rear)
- Suspension travel 220 mm

Safety & Assistance

- Petrol Range Extender (7-10kW)
- Anti-theft alarm & immobilizer system
- Electronic brake force distribution
- Intelligent Tyre Pressure Monitoring System (ITPMS)
- 3-point safety belts with pretensioners, load limiters

Interiors

- Camo fabric
- HEPA air-filter (Only with enclosed cabin version - NCB capability)
- Pressurized cabin, O2 supply, fire suppression
- Auto-Dimming: Rear view mirror